

CARACTERÍSTICAS DE HARDWARE

Interface	1 10/100/1000 Mbps RJ45 WAN Port 3 10/100/1000 Mbps RJ45 LAN Ports
Botón	Reset Button, WPS/Wi-Fi Button
Fuente de Alimentación Externa	12V/1A
Dimensiones (W X D X H)	7.2 × 3.7 × 1.3 in (182.7 × 94 × 33.3 mm)
Tipo de Antena	Four External antennas

CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos	IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11n/g/b 2.4 GHz
Frecuencia	2.4 GHz and 5 GHz
Tasa de Señal	1201 Mbps on 5 GHz, 300 Mbps on 2.4 GHz*
Funciones Inalámbricas	Enable/Disable Wireless Radio, WMM, Wireless Statistics, Band Steering
Seguridad Inalámbrica	WPA/WPA2/WPA3 encryptions
Potencia de Transmisión	CE: <20dBm (2.4 GHz), <23dBm (5.17 GHz–5.71 GHz) FCC:<30dBm (2.4 GHz & 5.15 GHz–5.825 GHz)
Calendarizar Inalámbricamente	Support 2.4 GHz and 5 GHz Wireless Schedule
Mesh Technology	EasyMesh Compatible, and support 802.11k/v/r

CARACTERÍSTICAS DE SOFTWARE

Características Avanzadas	Muti-SSID, Guest Network, QoS (Quality of Service), TX Beamforming, Fairness
Modos de Funcionamiento	Router, Access Point
WAN Type	Dynamic IP/Static IP/PPPoE/PPTP/L2TP (Multi-EWAN)
Administración	Local management: WebGUI management, Aginet app management Remote management: Aginet ACS, TR-069, TR-098, TR-181, TR-111, providers Aginet APP for end user (need to log in with TP-Link ID and bind your account)
DHCP	Server, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, NO-IP
VPN Pass-Through	IPSec, PPTP, L2TP
Control de Acceso	Parental Controls, White List, Black List
Seguridad de cortafuegos	DoS, SPI Firewall, IP and MAC Address Binding
Protocolos	IPv4, IPv6
Servidor VPN	PPTP, OpenVPN, IPSec

OTROS

Contenidos del Paquete	AX1500 Dual Band Gigabit Wi-Fi 6 Router EX141 Power Adapter RJ45 Ethernet Cable Quick Installation Guide
Requirements	Microsoft Windows 98SE/NT/2000/XP/Vista™/7/8/8.1/10, MAC OS, Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other J Subscription with an internet service provider (for internet access)
Ambiente	Operating Temperature: 0°C–40°C (32°F–104°F) Storage Temperature: -40°C–60°C (-40°F–140°F) Operating Humidity: 10%–90% non-condensing Storage Humidity: 5%–90% non-condensing