

## UniFi Express UXG-Lite



## Mechanical

---

<b>Dimensions</b>	98 x 98 x 30 mm (3.9 x 3.9 x 1.2")
<b>Weight</b>	320 g (11.3 oz)
<b>Enclosure material</b>	Polycarbonate

---

## Hardware

<b>Processor</b>	Dual-core ARM® Cortex®-A53 at 1 GHz
<b>Memory information</b>	1 GB DDR3L
<b>Management interface</b>	Ethernet Bluetooth 5.1
<b>Networking interface</b>	LAN: (1) GbE RJ45 port  WAN: (1) GbE RJ45 port
<b>Power method</b>	USB type C (5V/3A)
<b>Supported voltage range</b>	100–240V
<b>Max. power consumption</b>	3.83W
<b>Operating temperature</b>	-10 to 40° C (14 to 104° F)
<b>Operating humidity</b>	5 to 95% non condensing
<b>Certifications</b>	CE, FCC, IC

---

## Gateway Features

---

<b>Performance</b>	<ul style="list-style-type: none"> <li>WiFi QoS with UniFi APs</li> <li>Application, domain, and country-based QoS</li> <li>Application and device type identification</li> <li>Additional internet failover with LTE Backup</li> <li>Internet quality and outage reporting</li> </ul>
<b>Next-generation security</b>	<ul style="list-style-type: none"> <li>Application-aware firewall rules</li> <li>Signature-based IPS/IDS threat detection</li> <li>Content, country, domain, and ad filtering</li> <li>VLAN/subnet-based traffic segmentation</li> <li>Full stateful firewall</li> </ul>
<b>Advanced networking</b>	<ul style="list-style-type: none"> <li>License-free SD-WAN*</li> <li>WireGuard, L2TP and OpenVPN server</li> <li>OpenVPN client</li> <li>OpenVPN and IPsec site-to-site VPN</li> <li>One-click Teleport* and Identity Enterprise VPN**</li> <li>Policy-based WAN and VPN routing</li> <li>DHCP relay</li> <li>Customizable DHCP server</li> <li>IPv6 ISP support</li> </ul> <p>*When paired with a Cloud Key or Official UniFi Hosting. **When paired with a Cloud Key.</p>

---

## Application Requirements

<b>UniFi Network</b>	Version 8.0.7 and later
----------------------	-------------------------

---

