



ZKCF200

Passive Transceiver Pair



Technical Specifications

Model	ZKCF200
Properties	
Transmission Signal	1-channel
Transmission Distance	HDCVI 720P: max. 400m(1312.34ft) 1080P: max. 250m(820.21ft)
Category Type	UTP CAT 5E/6
Video Transmission Properties	
Coaxial Video Connector	BNC-M
Twisted-pair Video Connector	Push-terminal
Compatible Format	HDCVI/AHD/TVI/CVBS
Resolution	720P/1080P
Anti-interference	> 60db
Protection	
ESD	1a contact discharge electricity level 3
	1b air discharge electricity level 3
	Per: IEC61000-4-2
Coaxial Cable Connector	2KV(common-mode) Per: IEC61000-4-5
UTP Cable Connector	2KV(different-mode), 4KV(common-mode), Per: IEC61000-4-5
Impedance	
BNC Male	75 ohms
UTP Cable	100 ohms
Physical Properties	
Dimension(LxWxH)	180mmx19mmx16mm(7.09"x0.75"x0.63")
Shell	ABS
Color	Black
N.W.	42g/pair (0.09lb)
Stability	
MTBF	> 10000h
Environmental	
Operating Temperature	-10°C~+55°C(+14°F~+131°F)
Storage Temperature	-20°C~+70°C(-4°F~+158°F)
Humidity	0~95%(non-condensing)

Application



Package Information

- 1-Channel Passive HDCVI Balun ZKCF200 *1 pair