

UTP101P-HD4B Video Transceiver

Datasheet

4-Channel Passive HD (Unamplified) Video UTP Transceiver enables transmission of high-performance, real-time color or monochrome (B/W) CCTV video or HDCVI/AHD/HDTVI HD video over UTP cable , perfect for multipoint surveillance .

Model	UTP101 P-HD4
video port _	1 canal
	HDCVI-720P: 300 m; 1080P: 250 m; 400W (4MP): 200m; 800W (8MP): 150m
recommend distance	HDTVI-720P: 200 m; 1080P: 250 m;
transmission (with	300W (3MP): 250m ;
passive product)	AHD-720P / 960P: 200 m; 1080P: los 300m 400W (4MP): 200m; 500W (5MP): 150m Analog video : 500 m;
coaxial video port _	Puerto BNC macho
Pair video port _ _	2 channel push terminal _ _
braided	
compatibility of	Video HDCVI HDTVI AHD , PAL / NTSC / SECAM
video	
broadband _	0-75 MHz
protection against	
surges	2KV para: IEC61000-4-5
THAT	Contact discharge level 3 , 1 to , Air discharge level 3 , 1 b
working temperature _	-10-55°C
temperature of	
storage	-40°C-85°C
Humidity (Without	
condensation)	0-95%
outside shell	SECTION
Weight	18g