

Introduction

NG-C2300is an indoor security PT camera with a built-in WiFi module that simplifies installation wiring. This model has motion detection and other alarm message notification functions.

From the all-in-one smart home platform appNGTeco Home, you can handle various features such as two-way audio, real-time status notification, live HD video, or even review activity with local or cloud storage if needed.

NG-C2300It is the perfect choice for interior rooms in your home.

Characteristic



1080p Full HD Enjoy incredible 1080p sharpness on live video



Pan and tilt view Rotate and set the camera point of view through the app



Night vision See what happens even in the dark



Local and Cloud Storage Store and review recent activity with local or cloud storage



Bi-directional audio Listen or talk back and forth

specs

image sensing 1/2.7" CMOS Sensor Minimum illumination 0.1Lux/F1.2 Resolution 1080P (1920*1080) Pan and tilt view Pan 355 degrees Tilt 80 Focal length 3.6mm Field of view Horizontal view 85° Opening F2.0 Motion detection supports	degrees
Resolution 1080P (1920*1080) Pan and tilt view Pan 355 degrees Tilt 80 Focal length 3.6mm Field of view Horizontal view 85° Opening F2.0 Motion detection supports	degrees
Resolution 1080P (1920*1080) Pan and tilt view Pan 355 degrees Tilt 80 Focal length 3.6mm Field of view Horizontal view 85° Opening F2.0 Motion detection supports	degrees
Focal length 3.6mm Lens Field of view Horizontal view 85° Opening F2.0 Motion detection supports	degrees
Lens Field of view Horizontal view 85° Opening F2.0 Motion detection supports	
Opening F2.0 Motion detection supports	
Motion detection supports	
Alarm human detection N/A	
follow motion supports	
video compression H.264	
Video night vision 5 meters	
Frames per second 15f/s	
flip image supports	
audio compression PCM	
Audio detection distance 5 meters	
Speaker Incorporated	
dual-audio supports	
wireless protocol 802.11b/g/n (2.4GHz Wi-Fi)	
data security End-to-end encryption V	VEP/WPA/WPA2
Net Protocol WebRTC	
Cloud storage supports	
local storage Maximum support 256GB	
Power supply DC5V/1A	
Power adapter options US/EU/UK	
General Energy consumption 2W Watts (Max.)	
Work temperature - 10 ~ 60°C	
working humidity 20% ~ 95%	
Regulatory certifications CE/FCC	_

Application scenarios





Living room

children's room

Dimensions (mm)









