

G-C401

Semi-exterior Security Camera









1080p Vision Full HD nocturnal

n Storage nal Local and in the Cloud

Audio bidirectional



compatible with

GTeco HomeApp



Introduction

NG-C401it is a bullet-type camera for the security of any semi-outdoor environment that will always keep you informed of what is happening in the places of interest. The NGTeco bullet camera is equipped with a Wi-Fi module, which makes it easy to install and manage through the NGTeco Home mobile app. Also, 15M IR effective distance and 4 IR LEDs design will make sure almost everything is visible even in dark night.

With the NGTeco Home all-in-one smart home platform app, you can realize various powerful and useful functions such as two-way audio, real-time status notification, live HD video, or even review activity with local or online storage. the cloud if necessary.NG-C401It's an economical option and perfect for your backyard or garage.

Characteristic



1080p Full HD Enjoy 1080p high-resolution video monitoring



StorageLocal and Cloud
Store and review recent activity with local
or cloud storage



People Detection
Filter out objects and detect
only human movement



Two-Way Audio Listen or talk back and forth



Night vision Monitoring even in the dark



semi-outdoor Weatherproof design, can be used for semi-outdoor environment

specs

Camera	Image Sensor	1/3" 2MP CMOS
	Minimum Lighting	0.1Lux/F1.2
	Resolution	1920*1080 (1080p)
Lens	Focal length	3.6mm
	Field of view	100°(Diagonal) / 85°(Horizontal)
	Opening	F2.0
Alarm	Motion detection	supported
	People Detection	supported
Video	Video Compression	H.264
	Night vision	IR 15M Effective Distance, 4 IR LEDs
	Frames per second	25f/s
	Image Flip	yeseitherported
Audio	Audio Compression	G.711
	Scope	5m
	Speaker	Incorporated
	Two-Way Audio	supported
Net	Ethernet	1RJ-45 port (10/100Mbps)
	Wireless Protocol	802.11 b/g/n 2.4GHz Wi-Fi
	Data Security	End-to-end encryption, HTTPS
	Protocol	WebRTC
	Cloud storage	Supported (1 month free trial)
General	local storage	TF card up to 256GB
	Power supply	DC12V 1A
	Energy consumption	5W
	Current Options	US / EU / UK
	Operating Temperature	- 10°C up to 55°C
	Operating Humidity	10%~90%RH
	Certifications	FCC, CE, RoHS

Applicable Scenarios





semi-outdoor

Garage

Dimensions (mm)





