

DH-HAC-HFW1500CM(-A)

5MP Starlight HDCVI IR Bullet Camera



* The parameters and datasheets below can only be applied to 1500-S2 series.

- Max 25 fps@5MP (16:9 video output)
- CVI/CVBS/AHD/TVI switchable
- 2.8 mm fixed lens
- Max. IR length 30m, Smart IR
- Built-in mic(-A)
- IP67, 12V DC



System Overview

Experience 5MP full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 5MP HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance make the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700 m for 5MP HD video through coaxial cable, and up to 300 m through UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object comes closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu. This feature makes the camera compatible with most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4kV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification						WDR	DWDR
Camera						White Balance	Auto; manual
Image Sensor		1/2.7 inch CMOS				Gain Control	Auto; manual
Max. Resolution		2880 (H) × 1620 (V)				Noise Reduction	2D NR
Pixel		5MP				Smart IR	Yes
Scanning System		Progressive				Mirror	Off/On
Electronic Shutter Speed		PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s				Privacy Masking	Off/On (8 areas, rectangle)
S/N Ratio		> 65 dB				Certifications	
Min. Illumination		0.005 Lux/F1.6, 30IRE, 0 Lux IR on				Certifications	CE (EN 55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010+A1:2015, EN 55035:2017, EN 50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Illumination Distance		30 m (98.4 ft)				Port	
Illuminator On/Off Control		Auto; manual				Audio Interface	One channel built-in mic (-A)
Illuminator Number		3				Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Pan/Tilt/Rotation Range		Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°				Power	
Lens						Power Supply	12V ±30% DC
Lens Type		Fixed-focal				Power Consumption	Max 3.7W (12V DC, IR on)
Mount Type		M12				Environment	
Focal Length		2.8 mm				Operating Temperature	–40°C to +60°C (–40°F to 140°F); < 95% (non-condensation)
Max. Aperture		F1.6				Storage Temperature	–40°C to +60°C (–40°F to 140°F); < 95% (non-condensation)
Field of View		2.8 mm: 132° × 111° × 58° (diagonal × horizontal × vertical)				Protection Grade	IP67
Iris Type		Fixed iris				Structure	
Close Focus Distance		2.8 mm: 0.9 m (3.0 ft)				Casing	Metal throughout the whole casing
DORI Distance	Lens	Detect	Observe	Recognize	Identify	Camera Dimensions	166.6 mm × 69.7 mm × 70.0 mm (6.56" × 2.75" × 2.75")
	2.8 mm	63.6 m (208.7 ft)	25.4 m (83.3 ft)	12.7 m (41.7 ft)	6.4 m (21.0 ft)	Net Weight	0.33 kg (0.73 lb)
						Gross Weight	0.43 kg (0.95 lb)
Video							
Frame Rate		CVI: PAL: 5M@25 fps; 4M@25 fps; 1080P@25 fps; NTSC: 5M@25 fps; 4M@30 fps; 1080P@30 fps AHD: PAL: 4M@25 fps; NTSC: 4M@30 fps TVI: PAL: 4M@25 fps; NTSC: 4M@30 fps CVBS: PAL: 960H; NTSC: 960H					
Resolution		5M (2880 × 1620); 4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)					
Day/Night		Auto switch by ICR					
BLC		BLC/HLC/DWDR					

Ordering Information

Type	Part Number	Description
5MP Camera	DH-HAC-HFW1500CMP 2.8 mm	5MP HDCVI IR Bullet Camera
	DH-HAC-HFW1500CMN 2.8 mm	
	DH-HAC-HFW1500CMP-A 2.8 mm	
	DH-HAC-HFW1500CMN-A 2.8 mm	
	DH-HAC-HFW1500CMP 3.6 mm	
	DH-HAC-HFW1500CMN 3.6 mm	
	DH-HAC-HFW1500CMP-A 3.6 mm	
Accessories	DH-HAC-HFW1500CMN-A 3.6 mm	
	PFA134	Junction Box
	PFA130-E	IP66 Junction Box (For use alone or with PFA152-E pole mount)
	PFA152-E	Pole Mount Bracket (For use with PFA130-E junction box)
	PFM800-4K	Passive HDCVI Balun
	PFM321D	12V 1A Power Adapter
	PFM904	Integrated Mount Tester

Accessories

Optional:



PFA134
Junction box



PFA130-E
IP66 Junction Box
(For use alone or with
PFA152-E pole mount)



PFA152-E
Pole Mount Bracket
(For use with PFB204W)




PFM800-4K
Passive HDCVI Balun



PFM321D
12V 1A Power Adapter



PFM904
Integrated Mount Tester



Dimensions (mm[inch])

