

## Specification

Specification		
Part No.	LKV100USB	
Technical	Transmitter	Receiver
USB Compliance	USB2.0, compatible with USB1.1, USB1.0	
USB Rate	compatible with High-Speed, Full-Speed, Low-Speed	
Transmission Distance	CAT5E≤100m; CAT6/6A/7≤150m	
USB Device	Printer, camera, scanner, U disk, keyboard, mouse, touch screen	
Switch	support Gigabit switch extension	
USB Hot-Plug	support	
System	Windows、MacOS、Linux、Android	
Input	/	DC2.1×1, RJ45×1, USB-A ×4
Output	USB-A×1, RJ45 ×1	/
Network cable standard	CAT5E/CAT6/CAT6A/CAT7, follow IEEE-5688 standard	
Mechanical	Transmitter	Receiver
Housing	Iron	
Dimensions(L×W×H mm)	77.0(L) x 60.0(W) x 21.0(H) mm	
Net weight	123g	128g
Power supply	Power from the device	5V/1A
Power consumption	≤2W	≤2W
Operation temperature	-20~60℃	
Storage temperature	-30~70℃	
Relative humidity	0~90%(no condensation)	
Protection	Lightning Protection, Surge Protection, ESD Protection	
Application	Industrial Control, KVM Extension, Professional Audio-Visual, Security and monitoring, Medical Device Connectivity	

SHENZHEN LENKENG TECHNOLOGY CO.,LTD.

[www.lenkeng.net](http://www.lenkeng.net)

## Specification

Part No.	LQ100USB
参数	发射端
USB 兼容性	USB2.0, 兼容 USB1.1, USB1.0
USB 速率	兼容高速 (High-Speed), 全速 (Full-Sp
传输距离	CAT5E≤100m; CAT6/6A/7≤150m
USB 设备	支持打印机、摄像头、扫描仪、U盘、键
交换机	支持千兆交换机扩展
USB 热拔插	支持
支持系统	Windows、MacOS、Linux、Android
输入接口	/
输出接口	USB-A×1, RJ45 ×1
线材标准	CAT5E/CAT6/CAT6A/CAT7, follow IEEE-56
属性	发射端
材质	铁壳
尺寸	77.0(L) x 60.0(W) x 21.0(H) mm
重量	123g
电源	Power from the device
功耗	≤2W
工作温度	-20~60°C
储存温度	-30~70°C
相对湿度	0~90%(no condensation)
Protection	防静电、防雷击、防浪涌保护
应用场景	工业控制、KVM 扩展、专业视听、安防

接收端
eed), 低速 (Low-Speed)
键盘、鼠标、触摸屏
DC2.1×1, RJ45×1, USB-A ×4
/
i88 standard
接收端
128g
5V/1A
≤2W
监控、智慧医疗