

M70-4U-E

Multi-service Video Management Platform



Features :

- 19" standard 4U ATCA industry box
- Easy and flexible configuration with pluggable card module design
- 80ch@1080P or 320ch@D1 signal encoding (full configured)
- 80ch@4K or 320ch@1080P or 720ch@720P or 1500ch@D1 signal decoding (full configured)
- Support 320ch@1080P H.265 signal decoding(full configured)
- Support 240@D1 nonstandard stream signal decoding(full configured)
- Support max 60 screens splicing
- Support analog/digital video signals input and matrix output
- Support SD/HD video signal matrix switch and output
- Support non-compressed digital signal encoding output
- 6 RJ-45 gigabit network ports for matrix control, preview and online central storage
- Support TCP/IP/RTSP/RTCP/TCP/UDP/DHCP/PPPoE and etc. network protocols
- Remote cast analog/digital video onto the video-wall
- Remote reboot/upgrade/default setting and etc. operations
- Support VGA signal automatic adjustment

Technical Specification

Model

Model	M70-4U-E
-------	----------

System Parameter

Main Processor	Quad-core embedded microprocessor
Operating System	Embedded LINUX
Bus	PCI-E
Slot	12(2 Main Control Board Slot, 10 Video and Audio Function Board)
Mainframe	Power module (redundant power optional), main control board, control board, PCI-E bus rear panel, smart temperature controlled fan
Video Input Card	Max. 10
Video Output Card	Max. 10

Video Input





VEC0404HD-M70 (DVI)	Interface	4ch DVI-I (HDMI & VGA with convertor)
	Encoding Format	H.264/MPEG4
	Encoding Capability	4CH@1080P, support resolution: 1080P/720P/UXGA/SXGA+/SXGA/XGA/SVGA/VGA



VEC0404HH-M70 (HDMI)	Interface	4ch HDMI
	Encoding Format	H.264/MPEG4
	Encoding Capability	4CH@1080P, support resolution: 1080P/720P/UXGA/SXGA+/SXGA/XGA/SVGA/VGA
VEC3204FB-M70 (CVBS)	Interface	32ch BNC (1.0Vp-p, 75Ω)
	Signal Format	NTSC/PAL self-adaption
	Encoding Format	H.264/MPEG4
	Encoding Capability	32CH@D1
VEC0804HC-M70 (HDCVI)	Data Ports	2 RS485 ports
	Interface	8ch BNC (1.0Vp-p, 75Ω)
	Signal Format	HDCVI (audio/video/control)
	Encoding Format	H.264/MPEG4
	Encoding Capability	8CH@1080P

VEC0804HS-M70 (HD-SDI)	Interface	8ch BNC (1.0Vp-p, 75Ω)
	Signal Format	HD-SDI, 1.485Gbps
	Encoding Format	H.264/MPEG4
	Encoding Capability	8CH@1080P
	Data Ports	2 RS485 ports

Dimensions (mm/inch)



Video Output

VDC0605H-M70(HDMI)	Decoding Capability	8CH@12MP(15fps)/8CH@4K/32CH@1080P/72CH@720P/150CH@D1
	Interface	6ch HDMI
	H.265	32ch@1080P H.265 decoding
	Resolution	4000*3000@15fps, 3840*2160@30fps, 1920*1080@60fps, 1280*1024@60fps, 1280*720@60fps, 1024*768@60fps
	Split	1/4/6/8/9/16/25/36, free split

Video-Wall

Decoding Card Video-Wall Splicing	Splicing	Support video-wall splicing (max 60 LCD display units)
	Video-Wall	Support Splicing Zoom/Merge/ Roam/Overlay
	Input Source	HD/SD, Digital/Analog (support mixed input)
	Output Port	HDMI
	Control Mode	PC client-end/Local Operate Menu/Network Keyboard/IPAD

Network

Interface	6 RJ-45 ports (10/100/1000M), 2 in mainboard and 4 in control board
Serial Port	4 RS232 ports (4 RJ45), for console and control 1 RS485 port
USB	3 USB2.0, 1 USB3.0

Environmental

Power Supply	100~120V AC, 200~240V AC
Power Consumption	≤600W
Working Environment	-10°C ~+50°C / 10~90%RH / 86~106kpa
Dimension	4U, 482.6mm×496mm×177.8mm(W×D×H)
Weight	≤25Kg (full configured)

Ordering Information

Type	Part Number	Description
Video Management Platform	DH-M70-4U-E	4K, H.265 Decoding
	M70-4U-E	4K, H.265 Decoding