

Specifications		Description
Video signal	HDMI Input	1x HDMI
	HDMI Output	4x HDMI
	Compatibility	HDMI 1.4
		HDCP 1.4
	Resolutions	1080p@50/60Hz、720p@50/60Hz、 576p@50Hz、480p@60Hz 1920x1200、1280x960、1280x800、1280x768 、1680x1050、1360x768、1366x768、 1600x900、1024x768、800x600
Audio signal	3.5mm Output	PCM
	HDMI Output	PCM
Splice Settings	Mode	1x1/1x2/1x3/1x4/2x2
	DIP Switch	
	RS-232 (GND/RxD/TxD)	Default baud rate: 9600 Only when the DIP switch is set to "111", the mode can be switched via RS-232
Power	Power Supply	DC5V/1A
	Power Consumption	<4W
Operating Environment	Working temperature	-20℃~60℃
	Storage temperature	-30℃~70℃
	Humidity	0~90%RH (No condensation)
Physical Properties	Housing	Iron
	Weight	/
	Color	Black
	Dimensions	151.5(L)*86.5(W)*20.0(H)mm
Protection	ESD protection 1a Contact discharge level 2 (±4KV) 1b Air discharge level 3 (±8KV) Implementation of the standard: IEC61000-4-2	
	Lightning protection, Surge protection	