


Specification:

Material:

1. Plastic Housing :ABS
- 2.RJ45 contact material & finished:
 - 2-1.Phosphor Bronze with Nickel plated.
 - 2-2.Contact area : Gold plated.
- 3.IDC Housing: PC
- 4.IDC Terminal material & finished:
 - 4-1.Phosphor Bronze with Tin plated.
 - 4-2. Dual tool compatible.
 - 4-3. Suitable for 22-26 AWG stranded and solid wire.

Performance:

- a.The sticker color codes combine two wirings of T568A & T568B.
- b.Insertion Force: 900 gms for 8 contacts.
- c.Retention Strength: 7.7 kgs between Jack and Plug.
- d.Operation Temperature: -20° to 68°.
- e.Durability:
 - e-1. Jack : 750 cycles Plug-Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
 - e-2. IDC : Max. 200 punching times.
- f.The Cat.5e performance is in compliance with the ANSI/TIA/EIA 568C.2 standard.

A				Tolerance: X. ±0.5 .X ±0.3 .XX ±0.10	SCALE: FREE	CUSTOMER:				Approved by
					UNIT: mm			CUSTOMER P/N:	COMPANY P/N:	Checked by
				Angle: X° ±3° .X° ±1°	REV.: 00			DWG. No.:	TITLE: 24 PORT UTP cat5e PATCH PANNEL	Design by XJH
	REV.	DESCRIPTION	DATE							
	1		2	3			4	5	6	7